ROUTINE Orbit Siemens GO ALL

Indications	Trauma, Pain, Swelling					
Diagnostic Task	Detect fratures, edema, masses, or infection of the eye					
Position/Landmark	Head first- Supine					
Scan Type	Helical					
Topogram Direction	Lateral 30mA 130kV					
KV/Effective mAs	110kv 521mas					
Rotation time/pitch	1.0/0.55					
Detector Confituration	32x0.7					
table speed/Increment	12.32					
Dose Reduction	Cared dose 4D					
Allowed CTDI ranges*	30mGy-80mGy					
XR29 Dose Notification V	80mGy					
Helical Set-SUPINE	body	thickness			recon	
	recon part	spacing	kernel	window	destination	
	1 Orbit bone axial	.6mmx .6mm	Hr60	bone	pacs	
	2 Orbit soft tissue ax	ial 2mmx 2mm	Br40	mediastinum	pacs	
	3 Orbit soft tissue Co	r 2mmx 2mm	Br40	mediastinum	pacs	
	1cm superior to frontal sinus					
Scan start/end	through maxilla					
DFOV	25cm					
angle	none					
IV contrast volume/type	80ml under 250lbs 100ml over 250lbs isovue 370 2cc/sec if needed					
Scan delay	60 seconds					

Mark rt side of face with BB.

NOTE*

The Diagnositc Reference Dose (CTDI vol) is 75mGy(with 16cm CTDI phantom). The pass/fail limit (ACR and Washington state) is 80mGy. Most routine head scans on modern scanners have CTDIvol ranges between 40 and 60mGy.

^{*}The AAPM recommended NEXA XR29 Dose Notification Value for an adult head is 80mGy. The maximum CTDIvol should match the dose notification value. Exams with CTDI vol values less than the minimum allowed range should not be performed unless approved by a radiologist.